



Laser Handheld Barcode Scanner

► ZT-2152



Auto-Sensor



Drop Test 5M



USB&RS232



Plug & Play



Certificate

Features

- Decode most popular 1D barcodes
- Ready for all POS system and ideal for retail.
- With IP54 waterproof and dustproof protection.
- Plug and play, not need any driver, easy to operate.
- Ergonomic design, very comfortable operating sense.
- Using latest decoder technology, quick and fluent reading performance.
- Blue LED indicator and loud buzzer sound, can quick feedback reading codes.

TECHNICAL SPECIFICATION

OPERATIONAL PARAMETER

Light Source	Visible Laser Diode 650nm
Depth of Filed	0-280mm@UPC/EAN0.33mm PCS=90%
Scan Angle:	Elevation angle 65°/Tilt angle 30°/Declination 55°
Scan Rate:	300scans per second
Minimum Resolution	0.1mm(4mil)@ Code39, PCS=90% (Customizable 3mil)
Print Contrast:	More than 30% (UPC/EAN 100%)
Scan Model:	Manual,Hand
Visual Indicator:	Blue LED Lights , Buzzer
Host System Interfaces	HID USB, USB Virtual Com, Rs-232 Serial Port
Beeper Operation	Programmable tone & Volume

PHYSICAL CHARACTERISTICS

Dimension H x W x L:	173mm*67mm*94mm
Weight	220g (with cable)
Cable	Standard 1.8M straight
Material	ABS + PC

POWER PARAMETER

Input Voltage	5VDC±10%
Working current	85mA

ENVIRONMENTAL PARAMETER

Operating Temperature	0°C to 50°C
Working Humidity	5% to 95% relative humidity, non-condensing
Storage Temperature	-20°C to 60°C
Light Levels	0~4,000Lux(Fluorescence),0~100,000Lux(sunlight)
Drop Durability	Designed to withstand 5Meters drop

DECODE CAPABILITY

UPC/EAN/JAN,UPC-A & UPC-E,EAN-8 & EAN-13, JAN-8 &JAN-13, ISBN/
ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128,
Code 93,Interleaved 2 of 5 (ITF),Addendum 2 of 5, IATA Code,MSI/Plessey,
China Postal Code,Code 32 (Italian Pharmacode),RSS 14,RSS Limited,
RSS Expanded

